



T2100-ST1 treadmill

Advanced performance and reliability in exercise testing

The T2100-ST1 expands the reach of the T2100 treadmill series allowing installation at sites where 220V power is not available, without compromising performance. It features an extra-long, (63in , 160cm), and extra-wide (22 in, 56 cm) walking surface, as well as a zero-start feature that gradually increases speed for patient comfort and smooth operation. The T2100-ST1 can be stopped using several different methods to achieve the desired result. Decelerate slowly to a gradual stop using the emergency stop button, or stop quickly using the device keypad or the tether worn on the patient's wrist. All stop modes are available at all times giving the technician more control.

The optional adjustable height front handrail provides easy access to various size patients as needed.

With fewer moving parts than other treadmills, the T2100-ST1 treadmill delivers smooth, quiet operation that facilitates accurate stress testing acquisition—even at high workloads. The speed range of 0.1 to 15.0 mph, 0.2 to 24.0 km/h, self-calibrating and adjustable in 0.1 mph 0.1 km/h increments helps to maintain protocol accuracy and repeatability even when testing heavy patients.

Because it is part of the T2100 series, the T2100 ST-1 was designed as part of the GE Healthcare stress exercise solution, it communicates bi-directionally with GE Healthcare Stress ECG systems. This communication means both devices are constantly exchanging operating commands and data. This design helps to ensure device and procedural accuracy—and clinical confidence.



Feature highlights

- Smooth, quiet, zero-start, 4 HP (6 HP peak) hi-torque drive
- Smooth, quiet linear actuator elevation system
- Low-to-the floor, cushioned deck for patient comfort and safety.
- 22" x 63" (56 cm x 160 cm) running belt and handrails
- All steel chassis with powder coat finish
- Patented MasterTrack® belt alignment system eliminates off-center running belts
- Exceptionally accurate, self-calibrating speed and elevation
- Prominent emergency stop button and patient safety tether can be installed on either the left or right treadmill handle
- Minimum maintenance
- Optional height adjustable front handrail

Interface

- CASE™ Cardiac Assessment System for Exercise
- CardioSoft™ Diagnostic System multifunction PC-based diagnostic software

T2100 ST-1 treadmill

Safety Systems	<ul style="list-style-type: none"> • Dual comparative speed sensors • Auto runaway shutdown • Auto communication loss shutdown • Manual twist lock Emergency Stop button • Manual Stop Tether • Braking system for safe patient off-loading • Fire-rated motor pan hood enclosure
Weight	<ul style="list-style-type: none"> • Patient weight capacity 500 lb., 227 kg • Treadmill net weight: 425 lb., 193 kg
Drive System	<ul style="list-style-type: none"> • Heavy-duty 6-peak hp. brushless, DC servo motor
Power Requirements	<ul style="list-style-type: none"> • 110-120VAC, 1-phase, 60 Hz, 20-amp power supply • Must have dedicated 20A service
Speed Range	0.1 to 15.0 mph, 0.2 to 24.0 km/h, self-calibrating and adjustable in 0.1 mph 0.1 km/h increments.
Incline Range	0 to 25%, 0.5% incremental movements, self-calibrating.
Running Surface	<ul style="list-style-type: none"> • 22 in. x 63 in., 56 cm x 160 cm • MasterTrack® running belt tracking system • Cushioned running deck absorbs shock of foot falls • Self-lubricated and reversible running deck • Step-up, low profile deck height (7 in., 18 cm from floor)
Communication Ports	<ul style="list-style-type: none"> • RS232 Female Serial port • USB 1.0 "B" port
Floor Surface Footprint	33.0 in. x 78.5 in., 84 cm x 200 cm level surface.
Operating and Storage Condition Recommendations	<ul style="list-style-type: none"> • Operating Temperature Range: 4.5° to +38° C (+40° to +85° F) • Storage Temperature Range: -40° to +70° C (-40° to +158° F) • Operating and Storage Relative Humidity Range: 10% - 90%, non-condensing • Altitude: -50 to 5,280 feet
Optional Features	Adjustable height handrail: 31.2 in (79 cm) to 37.5 in (92.5 cm) as measured from the top of the running surface

Imagination at work

GE Healthcare
 9900 Innovation Drive
 Wauwatosa, WI 53226
 U.S.A.
www.gehealthcare.com

©2016 General Electric Company – All rights reserved.

General Electric Company reserves the right to make changes in specifications and features shown herein, or discontinue the product described at any time without notice or obligation.

GE, GE Monogram, Imagination at work, CASE and CardioSoft are trademarks of General Electric Company.

MasterTrack is a trademark of Full Vision Inc.

GE Healthcare, a division of General Electric Company.

DOC1895121